

ATHERECTOMY DEVICES

Company Name	Product Name	Minimum Vessel Diameter (mm)	Sheath Compatibility (F)	Crossing Profile (inch)	Working Length (cm)	Tip Length (cm)					
Cardiovascular Systems, Inc.	Diamondback 360° 1.25-mm Classic Crown	1.5	6	0.07 (1.8 mm)	145	1					
	Diamondback 360° 1.5-mm Classic Crown	1.75									
	Diamondback 360° 1.75-mm Classic Crown	2									
	Diamondback 360° 2-mm Classic Crown	2.25									
	Diamondback 360° 1.5-mm Solid Crown (30 µm)	1.75	6	0.07 (1.8 mm)	145	1					
	Diamondback 360° 1.75-mm Solid Crown (30 µm)	2									
	Diamondback 360° 2-mm Solid Crown (30 µm)	2.25									
	Diamondback 360° 2.25-mm Solid Crown (30 µm)	2.5									
	Predator 360° 1.25-mm Solid Crown (30 µm)	1.5	6	0.07 (1.8 mm)	145	1					
	Predator 360° 1.5-mm Solid Crown (30 µm)	1.75									
	Predator 360° 1.75-mm Solid Crown (30 µm)	2									
	Predator 360° 2-mm Solid Crown (30 µm)	2.25									
	Predator 360° 2.25-mm Solid Crown (30 µm)	2.5	7	0.089 (2.25 mm)	2	2					
	Covidien/ev3	TurboHawk LS-C	3.5–7	8	0.105 (2.7 mm)	110	6				
TurboHawk LX-C		7, 8						113	9		
TurboHawk LS-M										110	6
TurboHawk LX-M											
TurboHawk SX-C			2–4	6	0.085 (2.2 mm)	135	5.9				
TurboHawk SS-C		133						3.9			
TurboHawk SS-CL									149		
SilverHawk LS-M		4.5–7	7, 8	0.105 (2.7 mm)	110	6					
SilverHawk LX-M		4.5–6.5					113	9			
SilverHawk MS-M		3.5–5							110	6	
SilverHawk SXL		3–3.5	7	0.095 (2.4 mm)	136	7.2					
SilverHawk SS+				0.09 (2.3 mm)	135	2.6					
SilverHawk EXL		2–3	6	0.08 (2 mm)							
SilverHawk ES+		2–2.5		0.075 (1.9 mm)							
SilverHawk DS	1.5–2		0.073 (1.9 mm), 0.062 (1.57 mm) without wire								
Pathway Medical Technologies, Inc.	Jetstream Navitus	3	7	0.083 (2.1 mm)	135	N/A					
	Jetstream G3 SF	1.66, 1.85		0.073 (1.85 mm)							